

SAFETY DATA SHEET

1. IDENTIFICATION:

PRODUCT NAME: LUBRI-BOND 220 AEROSOL
 PRODUCT CODE: PLB220AEMSDS
 PRODUCT USE.: Low Friction Coating

HMIS CODES H F R P
 2*4 1 G

Manufacturer:

EVERLUBE PRODUCTS
 100 COOPER CIRCLE
 PEACHTREE CITY, GA 30269

EMERGENCY PHONE (24 hours): CHEMTREC - 800-424-9300
 INFORMATION PHONE (8:00 a.m - 5:00 p.m EST): (770) 261-4800
 NAME OF PREPARER: CHEMICAL COMMUNICATIONS COORDINATOR
 DATE PREPARED: 1/15/25

2. HAZARDS IDENTIFICATION



CLASSIFICATION:

Flammable Aerosol - Category 1
 Acute Toxicity, Dermal - Category 4
 Acute Toxicity, Inhalation - Category 4
 Acute Toxicity, Oral - Category 4
 Carcinogenicity - Category 1
 Serious Eye Damage - Category 1
 Reproductive Toxicity - Category 1B
 Skin Corrosion/Irritation - Category 2
 Skin Sensitization - Category 1
 Specific target organ toxicity, single exposure - Category 3

SIGNAL WORD:

DANGER

HAZARDS STATEMENT:

H222-Extremely flammable aerosol
 H280-Contains gas under pressure; may explode if heated
 H302-Harmful if swallowed
 H312-Harmful in contact with skin
 H315-Causes skin irritation
 H317-May cause an allergic skin reaction
 H332-Harmful if inhaled
 H336-May cause drowsiness or dizziness
 H350-May cause cancer
 H319-Causes serious eye Damage
 H360-May damage fertility or the unborn child
 H373-May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

P202-Do not handle until all safety precautions have been read and understood.
 P210-Keep away from heat/sparks/open flames/hot surfaces - No smoking
 P211-Do not spray on an open flame or other ignition source.

P242-Use only non-sparking tools.
 P251-Pressurized container: Do not pierce or burn, even after use.
 P260-Do not breathe dust/fumes/gas/mist/vapors/spray.
 P264-Wash hands thoroughly after handling
 P270-Do not eat, drink, or smoke when using this product
 P273-Avoid release to the environment
 P280-Wear protective gloves/eye protection/face protection.
 P301+P310-If swallowed, immediately call POISON CONTROL
 P302+P352-If on skin: Wash with plenty of water
 P304+P340-If inhaled: Remove person to fresh air and keep comfortable for breathing
 P305-If in eye rinse cautiously with water for several minutes.
 P308+P313-If exposed or concerned: Get medical advice/attention.
 P314-Get medical advice/attention if you feel unwell.
 P331-Do NOT induce vomiting
 P332+P313-If skin irritation occurs: Get medical advice/attention.
 P337+P313-If eye irritation persists: Get medical advice/attention.
 P362+P364-Take off contaminated clothing and wash it before reuse.
 P403-P233-Store in well-ventilated place. Keep container tightly closed.
 P403-P233-P410-P412-Store in a well ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 122°F/50°C.
 P501-Dispose of contents/container in accordance with local/regional/national/regulation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

	CAS#	% BY WT.
DIMETHYL ETHER	115-10-6	55 - 60%
LC50 (inhalation, rat) = 164,000 ppm for 4 hours		
METHYL ETHYL KETONE	78-93-3	20% - 25%
ACGIH TLV: 200 ppm		
ACGIH STEL: 300 ppm		
NIOSH REL: TWA 200 ppm		
NIOSH REL: TWA 590 mg/m3		
OSHA P0: TWA 200 ppm		
OSHA P0: TWA 590 mg/m3		
OSHA P0: STEL 300 ppm		
OSHA P0 STEL 885 mg/m3		
EC50 ALGAE ?100 mg/l 96 hr		
LD50 ORAL 3400.0 mg/kg (RATS)		
DC50 VAPORS 2000 PPM (RATS)		
LC50 FISH 100 mg/l 96 hr		
EC50 DAPHNIA >100 mg/l 48 hr		
CYCLOHEXANONE	108-94-1	5% - 10%
ACGIH TLV 20 PPM TWA		
ACGIH TLV 50 PPM STEL		
NIOSH REL 100 mg/m3		
NIOSH REL 25 PPM		
OSHA Z-1 200 mg/m3 PEL		
OSHA Z-1 50 PPM		
LD50 ORAL 1535 mg/kg (RAT)		
LD50 SKIN 948 mg/kg (rabbit)		
LC50 INHALATION: 8000ppm 4H (rat)		
LD50 ORAL 1400 mg/kg (mouse)		
LC50 FATHEAD MINNOW 481-578 mg/l 96 hr		
LC50 DAPHNIA 800 mg/l 24 hr		
ANTIMONY TRIOXIDE	1309-64-4	0% - 5%
ACGIH-TLV: 8 HR TWA-10 mg/m3, TOTAL		
ACGIH-TLV: 8 HR TWA-3 mg/3, RESPIRABLE		
OSHA-PEL: 8 HR TWA-15 mg/m3, TOTAL		

OSHA PEL: 8 HR TWA-5 mg/m3, RESPIRABLE LC50 INHALATION 4H RAT: >5.4 mg/l LD50 ORAL RAT: >5000 mg/kg		
XYLENE	1330-20-7	0% - 5%
ACGIH TWA: 100 PPM ACGIH STEL: 150 PPM OSHA Z-1 TWA: 100 PPM OSHA Z-1 435 mg/m3 LD50: ORAL 3,523 mg/kg (rat) LC50 INHALATION 6700 ppm (rat) 4hr EC50 ALGAE 4.36 mg/l 73 hr IC50 DAPHNIA 1 mg/l 24hr LC50 FISH 2.6 mg/l 96hr		
ETHYL BENZENE	100-41-4	0% - 5%
ACGIH: 20 ppm TWA OSHA 100 ppm TWA; 435 mg/m3 TWA OSHA 125 ppm STEL; 545 mg/m3 STEL NIOSH 100 ppm TWA; 435 mg/m3 TWA NIOSH 125 ppm STEL; 545 mg/m3 STEL LD50 ORAL: 3500 mg/kg (rat) LC50 Inhalation 17.2 mg/l 4h (rat) LD50 Dermal 15354 mg/kg (rabbit) LC50 FISH: 11.0-18.0 mg/l 96 hr EC50 ALGAE 4.6 mg/l 72 hr EC50 DAPHNIA 18.-2.5 mg/l 48 hr		
TOLUENE	108-88-3	0% - 5%
OSHA PEL 200.00 PPM-TWA OSHA PEL 300.000 PPM-CEILING OSHA VPEL 100.000 PPM-TWA OSHA VPEL 150.000 PPM-STEL (SKIN) ACGIH TLV 50.000 PPM-TWA (SKIN) ACGIH TLV 150.000 PPM-STEL (SKIN) LD 50 ORAL RAT: 2.6 g/kg LC 50 INHALATION RAT: 8000 PPM; 4 h LD 50 DERMAL RABBIT: 12,124 mg/kg LC50 FISH 7.63 mg/l 96 h EC50 INVERTEBRATES 8 mg/l 24 h EC50 ALGAE 10 mg/l 24h		
LEAD PHOSPHITE	12141-20-7	0% - 5%
ACGIH TLV-TWA: 0.15 mg/m3 (8 hrs), as Pb BLV: 50 mmg/100g blood OSHA PEL: 0.05 mg/m3, AS Pb		
ANTI-SKINNING AGENT	96-29-7	0% - 5%
LD/50 3680 mg/kg rat oral LD50 1-2 ml/kg Skin Rabbit		

4. First Aid Measures

Eyes:

With eyelids open, immediately flush eyes with lots of lukewarm water for at least 30 minutes. Get immediate medical assistance.

Skin:

Wash the skin thoroughly with plenty of water for at least 15 minutes, using a mild and non-abrasive soap. Cold water may be used. Consult a doctor if irritation persists.

Ingestion:

- Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airway free. Contact physician. Never give anything by mouth if victim is

rapidly losing consciousness, unconscious, or convulsing.

Inhalation:

Evacuate to fresh air and administer artificial respiration if breathing stopped. Obtain medical aid.

5. Fire Fighting Measures

Flammable Properties:

Flash Point (Degree F): -42F

Flash Point Method: TOC

Explosive Limits:

Upper explosive limit: 27.0%

Lower explosive limit: 1% (v)

Hazardous Combustion Products:

Oxides of Carbon, Aldehydes, Antimony fumes, Hydrogen Peroxide and their compounds

Extinguishing Media:

CO2, foam, dry chemical or halon

Firefighting Procedures:

Fire-Fighters should wear self-contained breathing apparatus and full protective equipment.

In case of fire, toxic fumes of lead oxide may be emitted.

6. Accidental Release Measures

Small Spill:

Eliminate all sources of ignition, provide ventilation, contain spill, and absorb with inert absorbent.

Issue warning "Flammable". Isolate the hazard area and restrict access.

Handle as highly flammable liquid

Wear appropriate breathing apparatus (if applicable) and protective clothing.

Prevent the spill or wash from entering sewers or watercourses

Large Spill:

Remove by mechanical means and place in containers.

Use only non-sparking tools and equipment.

Environmental Precautions:

Prevent product or wash waters from entering the water system or sewers.

US regulations require reporting spills of this material that could reach any surface waters. In Canada, report to the applicable provincial environment ministry.

7. Handling and Storage

Handling:

Maintain good personal hygiene. Avoid breathing processing vapors. Avoid prolonged or repeated skin contact. Wash skin with soap and water after handling. Wash contaminated clothing before re-use.

Storage:

Storage of individual cans should be done in an area below 120F, away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFP30B (Manufacture and Storage of Aerosol products) is recommended.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

Mixture, see section 3

Engineering Controls:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below the threshold limit values.

Use explosion-proof electrical/ventilating/lighting equipment.

Prevent the product or the wash waters from entering the water system or sewers.

Personal Protective Equipment:



Respiratory Protection:

In case of inadequate ventilation, wear respirator protection. Use NIOSH/MSHA approved Cartridge Respirator or Mask to keep airborne mists and concentrations below the time weighted threshold limit values.

Skin Protection:

Wear protective gloves (eg Neoprene or Nitrile) for skin protection.

Eye Protection:

Wear eye protection/face protection. Contact lenses should not be worn without goggles.

9. Physical and Chemical Properties

Flammability (solid, gas).....: Data not available

Boiling Point: 174 F

Melting Point: Data not available

VOC.....: 652 grams/liter

Freezing Point: Data not available

Flash Point: -42F

Vapor Pressure: Data not available

Vapor Density: 2.410 g/cc Maximum

Solubility in Water: Insoluble

Density.....: 7.4 lb/gal

Evaporation Rate: Data not available

Explosive Limits:

Upper Explosive Limit: 27.0%

Lower Explosive Limit: 1% (v)

Specific Gravity: .8887

PH: None known

Volatile (% by Weight).....: 85%

Appearance and Odor: Gray/Black liquid, organic solvent odor

Odor Threshold: Not applicable

Viscosity: <12.45mm²/s (mm²/s)

Partition Coefficient:.....: Data not available

Decomposition Temperature ...: Data not available

Autoignition temperature.....: 759.2 F

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):

Stable under normal conditions.

Incompatibility:

Oxidizers, Strong Acids or Alkalies.

Hazardous Decomposition Products:

Irritating and/or toxic fumes including the following may be released:
Oxides of Carbon, Aldehydes, Antimony fumes, Hydrogen Peroxide and their compounds

Hazardous Polymerization:

Will not occur.

11. Toxicological Information

Acute Toxicity Values:

Mixture, see section 3 - Hazardous Ingredients

Germ Cell Mutagenicity:

None of the ingredients are known or suspected of causing genetic defects.

Chronic/Carcinogenicity:

IARC (International Agency for Research on Cancer):

Group 1-Carcinogenic to humans

NTP (National Toxicology Program):

None known

Reproductive Toxicity:

Product contains chemical(s) that may damage fertility or the unborn child

STOT-single exposure:

May cause drowsiness or dizziness

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard:

May be fatal if swallowed and enters airways

Routes of Exposure:

Skin contact, skin absorption, eye contact, inhalation

12. Ecological Information

Environmental Fate:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Canadian and U.S. regulations require that environmental and/or other agencies be notified of a spill incident. The spill area must be cleaned and restored to the original condition or to the satisfaction of authorities.

Environmental Toxicity:

Data not available

Persistence and Degradability:

Data not available

Bioaccumulative Potential:

Data not available

Mobility in Soil

Data not available

Other Adverse Effects:

None known

13. Disposal Considerations

Disposal Methods:

Dispose of contents/container to: A licensed waste disposal facility.
Do not attempt to combust waste on-site. Incinerate at a licensed waste disposal site with approval of environment authority.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

UN Number:

UN 1950

UN Shipping Name:

Aerosols, Flammable

Transport Hazard Class:

Class 2.1

**Packing Group:**

Not applicable

ENVIRONMENTAL HAZARDS:**Marine Pollutant:**

None known

Special Precautions for User:

None known

15. Regulatory Information**U.S. Federal Regulations:****TSCA:**

ALL COMPONENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY OR ARE
EXTINCT FROM REQUIREMENTS

CERCLA: SARA Hazard Category:**Section 313:**

IF THIS MATERIAL HAS ANY COMPONENTS THAT ARE REPORTABLE UNDER SARA 313
THEY ARE SHOWN IN THE FOLLOWING LISTING. IF THE LISTING IS BLANK, THERE
ARE NO REPORTABLE COMPONENTS.

COMPONENT	CAS #	% BY WT.
Xylene	1330-20-7	0-5%
Antimony Trioxide	1309-64-4	0-5%

FRANK DODD SECTION 1502:

ALL COMPONENTS OF THIS PRODUCT COMPLY WITH TITLE 15 OF THE US CONSUMER
FINANCIAL PROTECTION ACT, DODD-FRANK ACT SECTION 1502 (CONFLICT
MINERALS ACT).

State Regulations:**California Prop 65:**

This product contains a chemical known to the State of California to
cause cancer.

This product contains a chemical known to the State of California to
cause birth defects or other reproductive harm.

International Regulations:

WHMIS:

A, B5, D1B, D2A, D2B

CEPA (Canadian Environmental Protection Act)

ALL INGREDIENTS ARE CEPA APPROVED FOR IMPORT TO CANADA. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATION (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

EINECS (European Inventory of Existing Chemical List)

ALL COMPONENTS OF THIS PRODUCT ARE INCLUDED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICALS LIST

16. Other Information

Date of Preparation: 1/15/25

KEY/LEGEND

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: International Carriage of Dangerous Goods by Road

RID: International Carriage of Dangerous Goods by Rail

CAS: Chemical Abstracts Service

CERCLA: Comprehensive Environmental Response, Compensation, & Liability Act

DOT: Department of Transportation

HMIS: Hazardous Materials Identification System

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

IDL: Immediately Dangerous to Life

IMDG: International Maritime Dangerous Goods

IMO: International Maritime Organization

LC: Lethal Concentration

LD: Lethal Dose

NIOSH: National Institute for Occupational Safety & Health

OSHA: Occupational Safety & Health Administration

PPM: Parts Per Million

REL: Recommended Exposure Limit

SARA: Superfund Amendments and Reauthorization Act

STEL: Short-term Exposure Limits

STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value

TSCA: Toxic Substances Control Act

TWA: Time Weighted Average

VOC: Volatile Organic Compounds

WHMIS: Workplace Hazardous Materials Information System

Manufacturer Disclaimer:

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION AND RECOMMENDATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION OR OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, IT IS THE USERS RESPONSIBILITY TO DETERMINE SAFETY, TOXICITY, AND SUITABILITY FOR HIS OWN USE OF THE PRODUCT. EVERLUBE PRODUCTS ASSUMES NO RESPONSIBILITY. THE CUSTOMER OR RECIPIENT OF THIS SDS SHOULD ENSURE THAT THE INFORMATION CONTAINED IN THIS SDS IS MADE AVAILABLE TO ALL EMPLOYEES OR OTHER PERSONS WHOM HE KNOWS OR BELIEVES WILL USE THIS MATERIAL