

Product Description

Vibra-Tite® Viz-Torque® 202 is an inspection lacquer used on completed fittings, assemblies, nuts, bolts and studs to show whether a part has been moved from its original position. Once dried in place, Viz-Torque 202 is dry and brittle which allows the film to quickly break in the case of tampering out in the field. Viz-Torque 202 has good adhesion to most metals when applied to a clean, dry surface.

Properties of Material

Chemical Type: Solvent – Isopropyl Alcohol

Appearance: Paste

Colors: – Orange, Blue, Green, Red, Yellow, Black, White, Gray, Pink

Solids: 43-47%

Viscosity: @ 25°C, cP

Brookfield RVT,

Spindle 5 @ 20 rpm: 11,000-18,000

Specific Gravity: 1.0

Tack-Free Time: 20seconds

Full Dry Time: 20 minutes

Temperature Range: -20°F - 300°F

Flash Point: 53°F (12°C)

Note: Drying time increases with increasing film thickness. High airflow can help aid the drying process.

Features

- Bright, highly visible colored paste that dries to a brittle film
- Brittle film that easily breaks when assembly has been tampered with
- Provides instant visual inspection to indicate loss of torque on an assembly
- Fluoresces under UV Light
- Provides professionally finished look to an assembly
- Material darkens when exposed to high heat

General Information

Storage

Product should be stored in a cool and dry location at temperatures between 32°F (0°C) to 86°F (30°C). Shelf life is 1 year from date of manufacture when stored at 72±8°F (22±4°C).

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information, or that use of the product will avoid losses or damages or give desired results. It is user's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. The user is advised to review the specific context of the intended use to determine whether the user's intended use violates any law or infringes upon any patent(s). No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

H.B. Fuller, Vibra-TITE, and Viz-Torque are registered trademarks of the H. B. Fuller Company.

vibra-tite-info@hbfuller.com